

GOLDEN SANDS SPEEDWAY & MARSHFIELD MOTOR SPEEDWAY

RULES FOR 2020 STOCK 6-CYLINDER DIVISION

ELIGIBLE MODELS

1. Any 6-Cylinder stock OEM car, truck or van. Minimum wheelbase of 97"
2. No 4-wheel drive (Activated) vehicles allowed.
3. Front/Rear Wheel Drive and American made vehicles ONLY.

INTERIOR

1. Dash, steering and pedals must remain stock. (Dash may be altered to accommodate any roll cage)
2. Racing seats are MANDATORY.
3. Interior floor pan must be complete. No holes.
4. All airbags must be removed.

BODY

1. Sun roof openings must be closed with steel.
2. Remove all glass except windshield. Broken glass must be cleaned from inside car before arriving at speedway. Lexan allowed with window bars.
3. Driver's door must be welded shut. Driver's door plate is mandatory.
4. Passenger door chained only.
5. Bumpers must be chained to frame.
6. Hood and trunk may be secured with hood pins.
7. Gutting only permissible on drivers door to allow for safety bars and door plate.
8. Working third brake light optional.
9. Stock ride height must be maintained.

ENGINE COMPARTMENT

1. Stock engine for that make and model from carburetor to the exhaust manifold.
2. Stock transmission.
3. Insulation under hood may be removed.
4. Battery may be placed within driver's compartment or in stock location, as long as it is Secured by minimum 1/8" x 1" steel strap with minimum 3/8" hardware with large head washers.
5. Exhaust complete and leak free. Maximum size of 2" O.D.. must run from engine to an area behind the driver. Mufflers are required and must exit behind drivers compartment.

SUSPENSION

1. Steering and suspension must remain stock. No modifications. Ride attitude must be maintained.
2. 1" camber allowed. Measured with a carpenter square.

3. Maximum 1" toe in or toe out allowed.

COOLING SYSTEM

Any radiator allowed which will fit in stock mounts. An overflow container mounted in engine compartment. Additives allowed in radiator. No anti-freeze.

GAS TANK

If gas tank is ahead of rear axle it may remain in place. If gas tank is behind axle it must be placed as far forward as possible, or replaced with a fuel cell or marine tank (max. 6.6 gal.). Must be secured by minimum 1/8" x 1" steel strap with minimum 3/8" hardware. Must be covered in hatchback in a metal case. All fuel systems must be sealed. No Alcohol based fuels allowed. A maximum of 110 octane fuel allowed.

TIRES

1. No 50 series, must be at least 60 series.
2. Must be DOT approved.
3. No racing tires.
4. Only tires speed rated M,N,P,Q,R,S,T or H allowed.
5. No tires rated U,V(VR), W(ZR), Y(ZR) or Z allowed.
6. Maximum footprint of 6.5"
7. No tire treating allowed.
8. Wheel size must be for that make and model. Same on all corners.

SAFETY

1. Helmet must meet minimum DOT standard, suggested Snell approved.
2. Gloves and long sleeves required.
3. Fire extinguisher required. 2 lb. BC rated mounted in quick release bracket within reach of driver.
4. Window nets are mandatory! Racing seatbelts are recommended.
5. Firewall must remain in tack.

ROLL BAR AND SIDE BARS

1. ROLL CAGES ARE MANDATORY. The material used must be 13/4 x .095 or better milled steel. No pipe fittings, exhaust pipe, or conduit.
2. Door bar or plate REQUIRED for four door hard tops with no door post.
3. The roll bar must be located directly behind the driver and reach as close as possible to the roof and the left side of car.
4. Two support bars must be added to roll bar to form a triangular, strong structure.
5. Driver compartment bracing must remain inside the driver's compartment and may not dissect, bisect or pass through either the engine or trunk firewall. Such bracing may be installed

as a safety feature only and may not reinforce the body or frame or alter the geometry of the car.

6. Roll bar installation is subject to inspection which will be closely scrutinized. Preferably, Roll cages can be purchased from Lefthander Chassis at an affordable cost.

CAR NUMBERS OR "NAMED CARS"

NOTE: Car may be given a "name". The "name" must be located on the doors and easily read from grandstands, and it must be in good taste (examples: "Club Forest Bar", "The Beast", "Thorp High School Shop Class"). You may use a sponsor, a theme or local school-be creative. If car has a name, the car number must be located on the rear quarter panel.

1. Minimum 18" high numbers in contrasting color. Without a "named car" Numbers must be on both doors and roof.
2. 6" number on upper right corner of windshield and on back of trunk - right side above tail light.
3. NO spray painted or "duct" tape numbers. Cars with non-legible numbers will not be scored.

GENERAL

All cars are subject to a minimum specification inspection at any time. It is the responsibility of the driver to prepare their car FREE of defects and in safe racing condition.